

▶ Unit A, 11F, Wing Hong Centre, 18 Wing Hong St., Kowloon, Hongkong

▶ 238, Alameda Dr. Carlos d'Assumpcao, Ed. Praca Kin Heng Long, 20G, Macau

Data sheet

Attenuators DC ~ 3GHz

Model No	DJRS0.5	DTJRN2	DJRN5	DJRN10	DTRN20	DTRN30
Frequency	DC~3GHz	DC~3GHz	DC~3GHz	DC~3GHz	DC~3GHz	DC~3GHz
Impedance (Ohms)	50	50	50	50	50	50
Attenuation (dB)	1~30dB	1~30dB	1~30dB	1~30dB	1~30dB	1~30dB
VSWR	1.20	1.15	1.20	1.20	1.20	1.20
Power rating Average (W)	0.5	2	5	10	20	30
Connector	SMA	N	N	N	N	N
Weight (g)	7	56	135	229	300	580
Dimensions D x L (mm)	8.3*28	20*58	30*58	48*95	54*99	54*109



Model No	DJRN50	DJRN80	DJRN100	DJSN150	DJSN200	DJSN300	DJSN500
Frequency	DC~3GHz	DC~3GHz	DC~3GHz	DC~3GHz	DC~3GHz	DC~3GHz	DC~3GHz
Impedance (Ohms)	50	50	50	50	50	50	50
Attenuation (dB)	1~30dB	1~30dB	1~30dB	1~30dB	1~30dB	1~30dB	1~30dB
VSWR	1.20	1.20	1.20	1.20	1.20	1.20	1.25
Power rating Average (W)	50	80	100	150	200	300	500
Connector	N	N	N	N	N	N	N
Weight (g)	500	535	840	2100	4200	5100	7500
Dimensions	64*122 D x L (mm)	68*132 D x L (mm)	80*165 D x L (mm)	160*130*65 (L*W*H mm)	230*160*87 (L*W*H mm)	300*160*86 (L*W*H mm)	400*245*97 (L*W*H mm)



Customisable: Size, shape (round / square), connector type (SMA, N, BNC etc.) and specifications