



▶ Unit A, 11F, Wing Hong Centre, 18 Wing Hong St., Kowloon, Hongkong



▶ 238, Alameda Dr. Carlos d'Assumpcao, Ed. Praca Kin Heng Long, 20G, Macau

Data sheet

Diplexer CDMA GSM DCS WCDMA / Wifi C250G70W100/W25

Specifications	CDMA GSM DCS WCDMA / Wifi	
Model	HM-C250/G70/W100	
Port	Mobile	WLAN
Frequency Range(MHz)	824-960, 1710-2170	2400-2500
VSWR	≤1.3	
Insertion Loss (dB)	≤0.7	≤0.7
Passband Ripple (dB)	≤0.5	≤0.5
Stopband Rejection (dB)	≥90	≥90
Intermod (dBc)	≤-140	
Max. Power (w)	100	
Impedance (Ω)	50	
Temperature Range (°C)	-30-65	
Dimension (mm)	158 x 82 x 42	
Connector type	N-K	

Features :

- 2-way or 3-way
- Top Quality Combiners
- Any Combination
- Coaxial Cavity Structure
- Reliable
- High Power Rating



Customizable to Customer Needs:

- N female or SMA connector
- Frequency Range
- Loss / VSWR

Also Available:

- 400 MHz Radio
- 800 MHz Tetra
- CDMA 1x
- CDMA 2000 evdo
- PHS / 3G
- DCS

