



▶ Unit A, 11F, Wing Hong Centre, 18 Wing Hong St., Kowloon, Hongkong



▶ 238, Alameda Dr. Carlos d'Assumpcao, Ed. Praca Kin Heng Long, 20G, Macau

Data sheet

Duplexer Series

SPECIFICATION

Model	DKDTETRA	DKDCDMA	DKDGSM	DKDDCS	DKDWCDMA
System	Tetra	CDMA	GSM	DCS	WCDMA
Frequency (MHz)	806-824 ul 851-869 dl	824-849 869-894	880-915 925-960	1710-1785 1805-1880	1920-1980 2110-2170
Isolation (dB min)	90	90	90	90	90
Insertion Loss (dB max)	1.3	1.3	1.3	1.3	1.3
VSWR	1.2	1.2	1.2	1.2	1.2
Power (W max)	100	100	100	100	100
Temperature (degree C)	-20 to +60	-20 to +60	-20 to +60	-20 to +60	-20 to +60
Connector	N female				
Dimension (mm)	108x82x49	121x121x44	172x88x37	123x104x35	147x91x30



Customizable to Customer Needs:

- N female or SMA connector
- Frequency Range
- Loss / VSWR

Also Available:

- 400 MHz Radio
- 800 MHz Tetra
- CDMA 1x
- CDMA 2000 evdo

