



▶ Unit A, 11F, Wing Hong Centre, 18 Wing Hong St., Kowloon, Hongkong



▶ 238, Alameda Dr. Carlos d'Assumpcao, Ed. Praca Kin Heng Long, 20G, Macau

# Data sheet

## Triplexer - GSM 900 / GSM 1800 /UMTS 2100

Specifications	GSM 900 / DCS1800 / WCDMA		
Model	HM-G80/D170/ /WC250A1		
Port	GSM	DCS	WCDMA
Frequency Range ( MHz)	880 - 960	1710 - 1880	1920 - 2170
VSWR	≤1.3		
Insertion Loss (dB)	≤0.8	≤0.8	≤0.8
Passband Ripple (dB)	≤0.6	≤0.6	≤0.6
Stopband Rejection (dB)	≥80		
Max. Power (w)	100		
Impedance (Ω)	50		
Dimension (mm)	123 x 147 x 66		
Temperature Range (°C)	-30 ~ 65		
Connector type	N Female		

### Combiner Series Features :

2-way and 3-way  
Top Quality Combiners  
Any Combination



### Customizable to Customer Needs:

- N female or SMA connector
- Frequency Range
- Loss / VSWR

### Also Available:

- 400 MHz Radio
- 800 MHz Tetra
- CDMA 1x
- CDMA 2000 evdo

