



▶ Unit A, 11F, Wing Hong Centre, 18 Wing Hong St., Kowloon, Hongkong



▶ 238, Alameda Dr. Carlos d'Assumpcao, Ed. Praca Kin Heng Long, 20G, Macau

# Data sheet

### Quadplexer - GSM 900 / GSM 1800 / WCDMA 2100 / Tetra 410

Port	GSM900 / DCS1800 / WCDMA2100 / Tetra410			
	GSM	DCS	WCDMA	Tetra
Frequency Range( MHz)	880 - 960	1710 - 1880	1920 - 2170	410 - 430
VSWR	≤ 1.5			
Insertion Loss (dB)	≤ 1	≤ 1	≤ 1	≤ 1
Passband Ripple (dB)	≤0.5	≤0.5	≤0.5	≤0.5
Stopband Rejection (dB)	≥50			
Max. Power (w)	100			
Impedance (Ω)	50			
Dimension (mm)	200 x 180 x 100			
Temperature Range (°C)	-20 ~ 60			
Connector type	N Female			

**Combiner Series Features :**

2-way 3-way or 4-way

Top Quality Combiners

Any Combination

Customizable to Customer Needs:

Also Available for :

- N female or SMA connector
- Frequency Range
- Loss / VSWR

- 400 MHz Radio
- 800 MHz Tetra
- CDMA 1x
- CDMA 2000 evdo
- PHS / 3G
- DCS
- Wifi 2.4G
- Wifi 5.8G

