



▶ Unit A, 11F, Wing Hong Centre, 18 Wing Hong St., Kowloon, Hongkong



▶ 238, Alameda Dr. Carlos d'Assumpcao, Ed. Praca Kin Heng Long, 20G, Macau

# Data sheet

## Quadplexer GSM / DCS / UMTS / LTE or WiMax

Model	DT09/18/21/27			
Port	GSM	DCS	UMTS	LTE or WiMax
Frequency Range ( MHz )	890-960	1710-1880	1920-2170	2500 - 2700
VSWR	≤ 1.3			
Insertion Loss ( dB )	≤ 1	≤ 1	≤ 1	≤ 1
Passband Ripple ( dB )	≤ 1	≤ 1	≤ 1	≤ 1
Stopband Rejection ( dB )	≥ 80			
Max. Power ( w )	100			
Impedance ( Ω )	50			
Dimension ( mm )	180x160x65			
Temperature Range ( °C )	-20 ~ 60			
Connector type	N Female			

**Combiner Series Features :**

- 2-way 3-way or 4-way
- Top Quality Combiners
- Any Combination



Customizable to Customer Needs:

- N female or SMA connector
- Frequency Range
- Loss / VSWR

Also Available:

- 400 MHz Radio
- 800 MHz Tetra
- CDMA 1x
- CDMA 2000 evdo

