



▶ A05, 9/F, Block 2, Camel Paint Building, 62 Hoi Yuen Road, Kwun Tong, Kowloon, HongKong



▶ 238, Alameda Dr. Carlos d'Assumpcao, Ed. Praca Kin Heng Long, 20G, Macau

Data *sheet*

Stadium Triband Antenna DTGWHPX5050M

Frequency	824-960 MHz / 1710-2170 MHz / 2300-2500MHz
Gain	9.5 dBi
Beamwidth horizontal	50° (3dB), <90° (20dB)
Beamwidth Vertical	50° (3dB), <90° (20dB)
Beam Tilt (manual)	0° -20°
Beamwidth at > 20 dB att.	>± 45° horizontal & vertical
Front to Back Ratio	>30dB
Return Loss	> 14 dB (VSWR 1.5)
PIM, 3rd Order 2 x 20 W	-140 dBc
Input Power per Port	50 watts
Polarization	824-2170MHz Vertical 2300-2500MHz ±45° MIMO
Impedance	50 ohm
Connector	2x 7/16 DIN female
Dimension	1359x852x140mm
Weight	32.5kg
Humidity	95%RH@+30°C
Temperature	-40°C to +70°C
Wind Speed, maximum	200.0 km/h
Radome Material	Fiberglass
Mounting	Mounting Kit included

824-960	1710-2170	2300-2500
SISO	SISO	MIMO

